



Nr. crt.	Buc.	Denumire	Caracteristici
1	1	Electropompa centrifuga Cod. F32/160B Italia	- Debitul: Q=10 - 25 m ³ /h - Presiunea: p= 5 - 6 bar - Tensiunea: 220 Vca/50 Hz - Puterea: 5,5 kW - Turatia: 2900 rot/min - Racord aspiratie: Dn 50 - Racord refularee: Dn 32
2	1	Supapa de siguranta DN 32 cu comanda manuala Model: SUPAPA 6302	- Diametrul nominal: DN 32 - Presiunea max: 40 bar - Presiune tarare: 0,5-10 bar - Material comp. : otel - Temperatura de lucru: -18...+300°C - Mediu de lucru: aer, apa, abur
3	2	Conducte cu bosaje DN 50 (2 m)	Teava zincata Ø63x2000
4	20	Duze pentru stropire	Diametre: 6, 8, 10 mm

Proiectat	Dr.ing. Cristescu C.	22CI-3.0 SH Inlocuieste nr.: Inventar nr.: SCHEMA HIDRAULICA instalatie stropire Masina ecologica de topit zapada
Desenat	Ing. Sefu S.	
Verificat	Ing. Dumitrescu L.	
Contr. STAS	Ing. Sacluc R.	
Aprobat	Dr.ing. Lepadatul I.	
INOE 2000-IHP		f.s. Data: 6.11.2017